

Picture

Model
E Series E560P
Video & Audio

Image Sensor

1/2.8" CMOS Sensor

Video Resolution

3840X2160(8Megapixels)@25FPS

Lens

2.8mm ~ 8mm, Zoom Module

Video Format

H.265

Field of View

Horizontal: 94° ~ 50°

Vertical: 53° ~ 30°

Day & Night

IR-cut filter with auto-switching

Infrared Night Vision

Up to 12 Meters (40ft)(LED: 12pcs/14mil/850nm)

Color Night Vision

4pcs/2.7W/6500K/180Lumens

Audio

Two-way Audio

Power

POE

IEEE 802.3af, 48V Active

DC Power

DC 12.0V~1A, <12W

Interface

Power

DC power port

System

Reset Button

Ethernet

One 10M/100Mbps RJ45

Storage

MicroSD card slot (Max. 256GB)

Audio

Built-in Microphone and Speaker

Pan&Tilt

Pan &Tilt Range

Pan: 355°, Tilt: 0°~50°

Auto Tracking

Support

Software Features

Frame Rate

Main Stream: 2fps - 25fps(default: 25fps)

Sub Stream: 4fps - 15fps(default: 10fps)

Code Rate

Main Stream: 4096Kbps -8192Kbps(default: 6144Kbps)

Sub Stream: 64Kbps - 512Kbps(default: 256Kbps)

Browser Supported

Edge, Chrome, Firefox, Safari

OS Supported

PC: Windows, Mac OS; Smartphone: iOS, Android

Smart Alarm

Motion detection/Human Detection/Vehicle Detection/Pet Detection

Record Mode

Motion Record/Schedule Record (Default: Motion Record)

Protocols & Standards

HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS,

FTP, P2P

Maximal User Access

Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)

20 Users (1 admin account & 19 user accounts);

Work with

Google Assistant, Reolink NVR

Working Environment

Temperature

Operating Temperature: -10°C~+50°C (14°F~122°F)

Humidity

Operating Humidity: 10% ~ 90%

Waterproof

IP65

Size & Weight

Dimension

Φ90 x 120mm

Weight

446g

Warranty

Limited Warranty

2-year limited warranty. For support, visit <https://support.reolink.com/hc/en-us/>