

P324

5MP PoE IP Camera with Person/Vehicle/Animal Detection

- Smart Person/Vehicle/Animal Detection
- Power over Ethernet
- 100ft Night Vision
- Audio Recording



Specifications

| Video & Audio | |
|-----------------------|---|
| Image Sensor | 1/2.7" CMOS sensor |
| Resolution | 2880x1615 (5 Megapixels)@30FPS |
| Lens | f=2.8mm/F1.6 IR CUT |
| Video Compression | H.264 |
| Field of View | Horizontal: 110° Vertical: 57° Diagonal: 133° |
| Day & Night | IR-cut filter with auto-switching |
| Infrared Night Vision | Up to 30 meters(100ft); LED:2pcs/1.8W/850nm |
| Color Night Vision | N/A |
| Frame Rate | Mainstream: 2fps - 30fps (default: 30fps) Substream: 4fps - 15fps (default: 10fps) |
| Code Rate | Main stream: 2048Kbps - 6144Kbps (default: 5120Kbps) |

| | |
|----------------------------|--|
| | Sub stream: 128Kbps - 1228Kbps (default: 1024Kbps) |
| Audio | Two way Audio |
| Power | |
| PoE | IEEE 802.3af, 48V Active |
| DC Power | DC 12.0V= 1A, <12W |
| Interface | |
| Power Port | DC power port |
| Reset Button | YES |
| Ethernet Port | One 10M/100Mbps RJ45 |
| Storage | MicroSD card slot (Max. 512GB); Reolink NVR |
| Audio In/Out | Built-in microphone & speaker |
| Software Features | |
| Browser Supported | Edge, Chrome, Firefox, Safari |
| OS Supported | PC: Windows, Mac OS; Smartphone: iOS, Android |
| Protocols & Standards | HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P |
| User Access | Max. 20 users (1 admin & 19 user); Max. 12 simultaneous streams (2 main & 10 sub streams) |
| Smart Alarm | Motion detection/Person Detection/Vehicle Detection/Animal Detection |
| Record Mode | Motion-triggered recording (default); Scheduled recording, 24/7 recording |
| Time Lapse | YES |
| Smart Home Compatibility | Google Assistant |
| Working Environment | |
| Temperature | Operating Temperature: -10°C~+55°C (14°F~131°F) |
| Humidity | Operating Humidity: 10% ~ 90% |
| Waterproof | IP67 |
| Size & Weight | |

| | |
|---------------------------|---|
| Dimension | Φ117x 103.8mm |
| Weight (Battery Included) | 526g |
| Warranty | |
| Limited Warranty | 2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ |

Gallery



- ① Mount
- ② Metal Aluminum Case
- ③ IR LEDs
- ④ High Definition Lens
- ⑤ Daylight Sensor



Manual rotation only



- ① Power Port
- ② Reset Button
- ③ Network
- ④ Waterproof Lid